

DESCRIPTION:

MicroKleen™ Spray & Equipment Cleaner AD1-919 is a pure grade of Isopropyl Alcohol (99% anhydrous). It is a flammable liquid and should be stored away from any possible sources of ignition; including pilot lights, electrical circuit boxes, electrical wiring, etc;

DO NOT SMOKE when working with MicroKleen™ AD1-919 (Pure Isopropyl Alcohol – anhydrous grade).

DIRECTIONS FOR USE:

MicroKleen™ Spray & Equipment Cleaner AD1-919 is used to clean and/or flush application tools and spray equipment, following the installation of Adsil Clear Inorganic Reacted Siloxane Protective Treatments.

MicroKleen™ AD1-919 can also be used to clean up drips, spills and over spray before the MicroGuard® Clear Reacted Siloxane products dry to touch. To clean up drips, spills and over spray, saturate clean cotton cloths with AD1-919 and wipe up before product dries. Always dispose of alcohol-saturated cloths in a safe and proper manner.

In certain situations, MicroKleen™ AD1-919 can be used to spot clean marine bright work, non-ferrous metals or stainless steel preliminary to the application of MicroGuard® Clear Inorganic Protective Treatments. Using a hand held spray-atomizing bottle, mist the area to be cleaned with AD1-919 and immediately wipe the area with a clean, white Micro-Fiber™ cloth. If the cloth soils during wiping continue cleaning process. Take care to exchange the cloths frequently. Dispose of alcohol saturated cloths in a safe and proper manner.

When ambient conditions are cooler, or in certain enclosed installation areas, MicroKleen™ AD1-919 may be used to reduce MicroGuard® Clear Inorganic Protective Treatments to promote more rapid solvent release and faster dry time. Refer to specific Technical Sheets for each individual MicroGuard® Clear Reacted Siloxane product for complete thinning instructions.

JOB SITE SAFETY:

Always wear safety glasses, latex gloves and a properly fitted respirator (NIOSH/MSHA – Black Cartridge, minimum) when working with MicroKleen™ AD1-919. Always read specific label cautions and MSDS before working with this Adsil product. Always have MSDS on file and available at the job site. Keep a fire extinguisher within easy access of the job site.

SITE CONTAINMENT:

Disposal of collected product, residues and clean up materials may be governmentally regulated. Observe all applicable local, state and federal waste management regulations pursuant to the use of MicroKleen™ Spray & Equipment Cleaner AD1-919.

Wipe up, mop up or soak up with absorbent material any spills of MicroKleen™ Spray & Equipment Cleaner AD1-919. Collect and hold for proper disposal.

For large industrial or shipping spills contact CHEMTREC for further instructions:

CHEMTREC @ 800-424-9300 INTERNATIONAL @ 703-527-3887 (collect)

Adsil, 1901 Mason Avenue, Suite 101, Daytona Beach, FL 32117 USA

PHONE: 386-274-1382 FAX: 386-274-1798 WEB: www.adsil.com

(Revision Date 05.11)

Advanced Siloxane Technology – Extreme Performance Product

MicroGuard®, Micro-Grip™ and MicroKleen™ are registered trademarks of Adsil.

Powered by:
Adsil
CORPORATION